



Specifications

Capacity (g)	32	210	410	810	2100	4100	8100
Readability (g)	0.002	0.01			0.1		0.5
Repeatability(Std. dev.) (g)	0.002	0.01			0.1		0.5
Linearity (g) (±)	0.002	0.01			0.1		0.5
Weighing Units	g, mg, kg, oz t, lb, GN, N, oz, taels (3), dwt, ct, ti, m, tola, custom						
Application Modes	parts count, percent weighing, animal weighing, checkweighing						
Stabilization Time	3 seconds						
Operating Temperature Range	50° - 104°F/10° - 40°C						
Power Requirements	AC Adapter (supplied) or 8-AA alkaline batteries (not included)						
Calibration*	InCal™ or external calibration mass (not included)						
Display (W x H) (in/mm)	LCD, 3.75 x 1.97/95 x 50, 6 - 13 segment alphanumeric, 6 - 7 segment numeric						
Pan Size (in / cm)	3/7.6 dia.	4.75/12 dia.			5.5 x 6/14 x 15		
Dimensions (WxHxD) (in/cm)	7.25 x 2.25 x 10.5 / 18.4 x 5.7 x 27						



Handing ApS

Nordkranvej 5-9, Vassingerød
DK - 3540 Lyngby
Tel.: +45 48160166
www.handing.dk

Ohaus Navigator Type N28110

Dette dokument er vejledende
Der tages forbehold for fejl.
This document is only guiding.
We make reservation for possible errors

Alle mål i mm.
Measures in mm

Lager nr. /sj
F775