

Types of design.

- Machines up to 800 including the box-section stand on a stable, welded base with two support columns and one lift support.
- From standard size 1000 with two support columns.
- Product touching parts in St37/St60 as standard, by wish in stainless steel 1.4541 or 1.4571 as well as special qualitys
- Mixing vessels with double jacket and double bottom for heating or cooling. They are also available as a pressure-tank with and without insulation.
- Clearance free outlet for connection to filling and dosing installations.
- Powder can be sucked in by running the machine under vacuum.
- Extra equipment (for example the vacuum pump, return flow cooling, temperature regulation, spray-nozzles) can be fitted to the standard machines.
- The complete mixing process can be electronically controlled.
- Fully automated tank arresting and opening system for automated processing.
- Latest standard safety equipment.
- Rotary mixing tools with pole switching over motor or with speed regulation.
- Mixing tools, generally with speed regulation.
- Design of speed control, depending upon requirements mechanically, hydrostatic or electronically.



Handing ApS

Nordkranvej 5-9, Vassingerød
DK - 3540 Lyngbe
Tel.: +45 48160166
www.handing.dk

Grieser Type VPLD30

Dette dokument er vejledende
Der tages forbehold for fejl.
This document is only guiding.
We make reservation for possible errors

Alle mål i mm.
Measures in mm

Lager nr.
R479