



Program memory:	10 Programs
LED digital indicator:	3 digits, 5/8" high
Timing range:	0-99.9 minutes
Amplitude:	0-99 linear scale
Sonic pulsing:	3600 pulses/min. @ 50/60Hz
Electromechanical tapping:	Switch selectable
Sieve capacity:	7 Standard sieves 3 Precision sieves
Cabinet:	Steel, baked painted finish, light, sliding acrylic door
Electrical:	230/115V selectable; 40 Watts max.
Memory:	Nonvolatile RAM
Dimensions:	10x10x20" WxDxH (254x254x508mm)
Net weight:	37 lb (16.8kg)

Maximum sample quantity for woven-wire sieves 38mm (#400) or larger is 20g or 7cc. For finer woven-wire sieves, 10g or 4cc is the maximum. For precision sieving with electroformed sieves, a one gram sample is typical and 5 grams or 5cc is maximum.



Handing ApS
 Nordkranvej 5-9, Vassingerød
 DK - 3540 Lyngbe
 Tel.: +45 48160166
 www.handing.dk

Gilson Type GA-6

Dette dokument er vejledende
 Der tages forbehold for fejl.
 This document is only guiding.
 We make reservation for possible errors

Alle mål i mm.
 Measures in mm

Lager nr. /sj
SF078